



TUBIGOMMA DEREGBUS S.R.L.
 ITALIA -35030 Saccolongo (PD) Via E. Mattei n° 1
 Tel. +39-049-8016155 Fax. +39-049-8015834
www.tuder.com

ABRASIVO/40



DATA SHEET

High performance abrasion resistant delivery hose of pre-mixed materials. Tube and cover are electrically conductive for static dissipation.

CONSTRUCTION

- **Tube:** smooth, black SBR/NR conductive rubber, abrasion resistant tube
- **Reinforcement:** textile plies.
- **Cover:** smooth, black SBR/NR conductive rubber, abrasion resistant, cloth finish.
- **Marking:** TUDER.COM - TUBIGOMMA DEREGBUS SRL – ITALY - ABRASIVO/40 W.P. 40 BAR (W.P. 600 PSI)

TECHNICAL CHARACTERISTICS

Max working pressure: 1/3 of the burst pressure.
Vacuum :
Temperature range: - 30° C / + 80° C.
Applicable Specification: dimensional tolerances as per ISO 1307-1997.

diametro interno <i>inside diameter</i>		diametro esterno <i>outside diameter</i>		pressione di eserc. <i>working pressure</i>		press. di scoppio <i>bursting pressure</i>		peso <i>weight</i>		Note
mm	inch	mm	inch	bar	psi	bar	psi	Kg/m	lbs/ft	
63,5	2-½	85	3-11/32	40	600	120	1800	2,95	1,98	

Other sizes available on request