



**TUBIGOMMA DEREGIBUS** S.R.L.  
 ITALIA -35030 Saccolongo (PD) Via E. Mattei n° 1  
 Tel. +39-049-8016155 Fax. +39-049-8015834  
[www.tuder.com](http://www.tuder.com)

# DRY CEMENT DELIVERY



## DATA SHEET

Abrasion resistant hose for discharge of dry cement. Tube and cover are electrically conductive for static dissipation.

## CONSTRUCTION

- **Tube:** smooth, black SBR/NR abrasion resistant conductive rubber,
- **Reinforcement:** textile plies.
- **Cover:** smooth, black SBR/NR conductive rubber, abrasion resistant, cloth finish.
- **Marking:** to be identified

## TECHNICAL CHARACTERISTICS

**Max working pressure:** 1/3 of the burst pressure.

**Vacuum:**

**Temperature range:** - 30° C / + 80° C.

**Applicable Specification:** dimensional tolerances as per ISO 1307-1997.

diametro interno <i>inside diameter</i>		diametro esterno <i>outside diameter</i>		pressione di eserc. <i>working pressure</i>		press. di scoppio <i>bursting pressure</i>		peso <i>weight</i>		Spessore sottostrato <i>tube thickness</i>	
mm	inch	mm	inch	bar	psi	bar	psi	Kg/m	lbs/ft	mm	inch
76	3	88	3,47	3	45	9	135	1,89	1,27	3	1/8
102	4	114	4,47	3	45	9	135	2,49	1,67	3	1/8
114	4-1/2	126	4,97	3	45	9	135	2,76	1,85	3	1/8
127	5	139	5,47	3	45	9	135	2,90	1,94	3	1/8
152	6	164	6,47	3	45	9	135	3,71	2,49	3	1/8
168	6-5/8	180	7,10	3	45	9	135	4,09	2,74	3	1/8
102	4	117	4,61	5	75	15	225	3,33	2,23	4,8	3/16
102	4	120	4,73	5	75	15	225	3,87	2,59	6	1/4

Other sizes available on request