

TUBO P.T.F.E. TIPO TP1

TF00TP1

APPLICATIONS :



Hose for use with IMM Hydraulics fittings. Standard tail.

Internal hose: Smooth P.T.F.E. medium thickness wall.

Covering: 1 high tensile stainless steel AISI 304 wire braids.

Operating temperature: from -70 to +260°C.

Part number	ID			Spessore parete	OD mm	Max WP(23C°)		Min BP(23C°)		Min BR		Ferrule
	in	mm	Dash			bar	psi	bar	psi	inch	mm	
	TF00TP1-03	3/16"	4.8			03	0.9	7.8	210	3045	840	
TF00TP1-04	1/4"	6.35	04	0.9	9.4	185	2683	740	10730	1.772	45	*
TF00TP1-05	5/16"	7.9	05	0.9	11.2	160	2320	640	9280	1.969	50	*
TF00TP1-06	3/8"	9.5	06	0.9	12.8	140	2030	560	8120	2.165	55	*
TF00TP1-07	13/32"	10.3	07	0.9	13.6	135	1958	540	7830	2.559	65	*
TF00TP1-08	1/2"	12.7	08	0.9	16	125	1813	500	7250	2.756	70	*
TF00TP1-10	5/8"	15.9	10	1	19.4	105	1523	420	6090	5.118	130	*
TF00TP1-12	3/4"	19	12	1	22.5	95	1378	380	5510	7.480	190	*
TF00TP1-14	7/8"	22.2	14	1.1	26	75	1088	300	4350	9.843	250	*
TF00TP1-16	1"	25.4	16	1.1	29.4	67	972	268	3886	10.630	270	*

(*) - For temperature over 100°C, please contact our technical department