



TUBIGOMMA DEREGBUS S.R.L.
 ITALIA -35030 Saccolongo (PD) Via E. Mattei n° 1
 Tel. +39-049-8016155 Fax. +39-049-8015834
www.tuder.com

VAPORE/17 NR T 232 *C



DATA SHEET

Steam hose red cover 17 atm 232 *C (250 psi, 450 *F) continuous service

CONSTRUCTION

- **Tube:** smooth, black sintetic rubber
- **Reinforcement:** high tensile steel plies.
- **Cover:** pin pricked, smooth, red sintetic rubber, cloth finish.
- **Marking:** TUDER.COM - TUBIGOMMA DEREGBUS SRL – ITALY - STEAM HOSE – W.P. 250 PSI 450 D.F. – W.P. 17 BAR 232 D.C. – DRAIN AFTER USE

TECHNICAL CHARACTERISTICS

Max working pressure: see the below chart .
Vacuum :
Temperature range: - 40° C / + 232° C.
Applicable Specification: dimensional tolerances as per ISO 1307-1997.

diametro interno <i>inside diameter</i>		diametro esterno <i>outside diameter</i>		pressione di eserc. <i>working pressure</i>		press. di scoppio <i>bursting pressure</i>		peso <i>weight</i>		raggio di curvatura <i>bending radius</i>	
mm	inch	mm	inch	bar	psi	bar	psi	Kg/m	lbs/ft	mm	inch
10	3/8	22	7/8	17	250	170	2500	0,45	0,30		
13	1/2	25	1	17	250	170	2500	0,53	0,36		
19	3/4	32	1-1/4	17	250	170	2500	0,76	0,51		
25	1	39	1-17/32	17	250	170	2500	1,00	0,67		
32	1-1/4	46,5	1-53/64	17	250	170	2500	1,35	0,90		
38	1-1/2	54	2-1/8	17	250	170	2500	1,65	1,11		
51	2	68	2-11/16	17	250	170	2500	2,32	1,55		
63,5	2-1/2	84	3-5/16	17	250	170	2500	3,70	2,48		
76	3	101	3-31/32	17	250	170	2500	5,30	3,56		
102	4	128	5-3/64	17	250	170	2500	8,70	5,84		

Other sizes available on request